## AIR CORPS INFORMATION CIRCULAR

#### (AVIATION)

PUBLISHED BY THE CHIEF OF AIR CORPS, WASHINGTON, D. C.

Vol. VI

May 21, 1927


No. 586

# STUDY OF BALANCED RUDDERS

 $\nabla$ 

Prepared by J. A. Roche Matériel Division, Air Corps McCook Field, Dayton, Ohio February 16, 1927





19980820 006

UNITED STATES
GOVERNMENT PRINTING OFFICE
WASHINGTON
1927

This property for

Certificate: By direction of the Secretary of War the matter contained herein is published as administrative information and is required for the proper transaction of the public business.

(ii)

### STUDY OF BALANCED RUDDERS

#### OBJECT

The object of this study was to discover to what extent the rudder can be balanced without causing pilots to complain of an overbalanced condition.

#### DISCUSSION


The dimensions of the various rudders in use on military airplanes were collected and an expression was developed to show the relative extent to which these rudders are balanced. The development of this expression assumed a uniform load distribution on the balanced portion and a gradually decreasing load from the hinge to the trailing edge. The coefficient K<sub>b</sub> is, therefore, a ratio of the balanced area to the area aft of the hinge, due weight being given to the effectiveness of both areas. Pilots observations on the action of these rudders were also obtained and are given under the heading of "Remarks" in the table below.

#### CONCLUSIONS

This study shows no definite relation between the balanced coefficients and the pilots remarks. It may, of the alleged overbalanced XO-6.

therefore, be that rudders which are reported as overbalanced are really not overbalanced, and that other yaw characteristics of the airplane have resulted in producing that impression on the pilot. Again it may be that the shape of the balanced area influences its effectiveness in a way which we are unable to understand, still another possibility is that the area aft of the hinge may be shielded to various extents in the different airplanes by the fuselage, stabilizer, and elevators, also to an extent which we can not quantitatively determine. It is noteworthy that the XO-6 airplane has the smallest balance coefficient and yet is criticized by the pilots for being overbalanced. In view of our further study of the yaw characteristics of this airplane it is fairly safe to conclude that the overbalanced feeling is due to certain irregularities in the yaw moment curves for which either the nose of the airplane or the nose of the fin may be responsible. It is also worthy of note that the DH-4, the rudder characteristics of which are satisfactory, shows the highest value of balance coefficient and that this coefficient is more than three times as great as that

#### DATA ON RUDDER BALANCES OF VARIOUS AIRPLANES



 $A_t = \text{Total Area of Rudder}$ 

A<sub>a</sub>=Area aft of hinge center line

Ab=Area of balance fore of hinge center line

C<sub>a</sub>=Mean Chord of A<sub>a</sub>

 $C_b = Mean Chord of A_b$ 

 $X_a = \frac{C_a}{2} = \text{Dist. to C. P. of } A_a \text{ (approximate)}$ 

 $X_b = Distance$  to center of area  $A_b$   $K_b = \frac{Moment \text{ of } Load \text{ on } A_b}{Moment \text{ of } Load \text{ on } A_b} = \frac{2 A_b}{A_b}$  $K_b = \frac{Moment of Load on A_a}{Moment of Load on A_a}$ 

Airplane	Rudder	Remarks	Reference	At	Aa	Аь	Ca.	Сь	X.	Хь	Кь
CO-6	Suggested ch	O. K O. K O. K O. S Overbalanced O. K Overbalanced O. K Very good Overbalanced Overbalanced Overbalanced Overbalanced	dodododododododo.	Sq. ft. 14. 82 14. 27 18. 41 13. 70 9. 35 12. 20 11. 80 10. 80 13. 75 36. 40 34. 00 13. 32 17. 27 14. 92 14. 49	Sq. ft. 12. 73 16. 50 12. 32 7. 69 10. 40 10. 60 9. 32 11. 90 30. 54 30. 54 11. 98 15. 80 13. 65 12. 65	Sq. ft. 2. 09 1. 54 1. 91 1. 38 1. 66 1. 80 1. 20 1. 48 1. 85 5. 86 3. 46 1. 34 1. 47 1. 27 1. 84	In. 25. 50 28. 60 24. 95 22. 15 23. 60 22. 00 22. 18 29. 60 46. 90 46. 90 26. 50 26. 50	In. 12. 10 8. 88 15. 30 8. 25 10. 12 12. 50 10. 13 16. 40 7. 82 20. 85 23. 70 16. 05 8. 39 9. 50 14. 15	In. 8.50 8.50 9.53 8.32 7.38 7.39 9.87 15.63 15.63 9.60 8.97 8.33 8.83	In. 7. 02 4. 94 8. 60 3. 93 5. 24 7. 87 5. 94 6. 65 3. 97 12. 51 14. 20 8. 24 4. 32 5. 09 7. 33	0. 260 141 209 106 306 346 184 286 125 307 206 192 089 114 241

<sup>&</sup>lt;sup>1</sup> Triangular distribution of load is assumed for  $A_a$ . Uniform distribution is assumed for  $A_b$ . <sup>2</sup> Insufficient total area for control at low speeds.

